

Znakovi za dizalice



OP-15



DI-01



DI-02

STANDARDNE DIMENZIJE	A4 (297x210 mm)	A5 (210x148 mm)
STANDARDNI MATERIJALI	naljepnica	plastika

Primerak izabir	DOPUŠTENO OPTEREĆENJE ČELIČNE UŽADI				
	kut do 0°	kut do 45°	kut do 90°	kut do 120°	
10	5.19	10.39	9.41	7.25	5.19
12	8.04	16.08	14.71	11.18	8.04
14	9.81	19.61	17.65	13.73	9.81
16	11.77	23.54	21.18	16.48	11.77
18	14.71	29.42	26.48	20.59	14.71
20	19.61	39.23	35.3	27.46	19.61
22	23.54	47.07	42.17	31.38	23.54
24	31.38	62.76	55.89	44.13	31.38
26	39.23	78.45	70.61	54.92	39.23
28	49.03	98.07	88.26	68.65	49.03
30	58.84	117.68	105.91	82.38	58.84

Primerak izabir	DOPUŠTENO OPTEREĆENJE LANCA				
	0°	kut do 0°	kut do 45°	kut do 90°	kut do 120°
5	2.45	4.9	4.41	3.43	2.45
6	3.43	6.86	6.37	4.81	3.43
7	4.41	8.82	7.84	6.18	4.41
8	6.18	12.36	11.08	8.63	6.18
10	9.81	19.62	17.65	13.73	9.81
13	15.69	31.38	28.44	22.06	15.69
16	24.52	49.03	44.13	34.32	24.52
18	30.89	61.78	54.92	43.15	30.89
20	39.23	78.45	70.61	54.92	39.23
23	49.03	98.07	88.26	68.65	49.03
26	61.78	123.56	110.82	86.29	61.78

DI-03

SIGNALIZACIJA PRI RADU S DIZALICOM		
ZAHVAT TERETA	DIZANJE	SPUŠTANJE
LJEVO	DESNO	NAPRIJED
NATRAG	USPRAVNO POSTAVLJANJE	VODORAVNO POSTAVLJANJE
STOJ	KRAJ RADNJE	OPASNOST ŽURNO ZAUSTAVLJANJE

DI-04

STANDARDNE DIMENZIJE	A4 (297x210 mm)	A5 (210x148 mm)
STANDARDNI MATERIJALI	naljepnica	plastika